MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

COMPANY NAME : Hakko Corporation

ADDRESS: 4-5, Shiokusa 2-chome, Naniwa-ku, Osaka, 556-0024 Japan

SECTION IN CHARGE : Research & Development Center

EMERGENCY TELEPHONE : 81-6-6561-3225 (FAX: 06-6568-0821)

NUMBER/REFERENCE: Sales Division

PRODUCT NAME: Chemical paste

Model: FS100-01

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION

Physical and chemical hazards

Explosive substance : Unclassifiable

Flammable gas : Not eligible for classification

Flammable aerosol: Not eligible for classification

Oxidizing gas : Not eligible for classification

Compressed gas : Not eligible for classification

Flammable liquid : Not eligible for classification

Flammable solid : Unclassifiable

Self-reactive substance : Unclassifiable

Pyrophoric liquid: Not eligible for classification

Pyrophoric solid: Unclassifiable

Self-heating substance : Unclassifiable

Substance which, in contact with : Unclassifiable

water, emits flammable gases

Oxidizing liquid: Not eligible for classification

Oxidizing solid: Not eligible for classification

Organic peroxide: Not eligible for classification

Corrosive to metal : Unclassifiable

Health hazards



Acute toxicity - Oral : No category

Acute toxicity - Dermal : Unclassifiable

Acute toxicity - Inhalation: gas : Not eligible for classification

Acute toxicity - Inhalation: vapor : Unclassifiable

Acute toxicity - Inhalation: dust : Unclassifiable

Acute toxicity - Inhalation: mist : Not eligible for classification

Skin corrosion · Skin irritation : No category

Serious eye damage /Eye irritation : Category 2B

Respiratory sensitizer: Unclassifiable

Skin sensitizer : Unclassifiable

(Germ-cell mutagenicity) : Unclassifiable

(Carcinogenicity): Unclassifiable

Reproductive toxicity: Unclassifiable

Specific target organ systemic : Category 3 (respiratory tract irritation)

toxicity - single exposure

Specific target organ systemic : Category 1 (lung and liver)

toxicity – repeated exposure

Aspiration hazard: Unclassifiable

Environmental hazards

Acute hazards to the aquatic : Unclassifiable

environment

Chronic hazards to be the aquatic : Unclassifiable

environment

GHS LABEL ELEMENTS

PICTOGRAM OR SYMBOL





SIGNAL WORD : Danger

HAZARD INFORMATION : Eye irritation

Damage to organs (lungs)
Potential respiratory irritation



PRECAUTIONS

[SAFETY MEASURES] : Do not handle the product until you read and understand all the safety precautions.

When using the product, do not eat or smoke.

Avoid exposure by using protective equipment for personal use and a ventilator.

Use respiratory protective equipment.

Use protective gloves, clothes, glasses, and mask.

Use the product only outdoors or a well-ventilated area.

Do not allow the product to come into contact with the eye, skin, or clothes.

Do not inhale dust and fume.

After handling the product, well wash the hands.

Avoid release to the environment.

[FIRST AID MEASURES] : Inhalation: Move the victim to a location with fresh air and rest him in the easy-to-breath position. Immediately receive medical attention.

> Ingestion: Rinse the mouth. Do not force the victim to vomit. Immediately receive medical attention.

> Eye contact: Carefully rinse the eye with water for several minutes. If the contact lens can be removed easily, do so before rinsing. Immediately receive medical attention.

Skin contact: Rinse the skin with a large amount of water and soap. Receive medial attention.

Wear contact: Immediately remove all the contaminated clothes. To reuse contaminated protective wear, machine-wash it.

Exposure or potential exposure: Receive medial attention.

Sick feeling: Receive medial attention.

Collect leakage.

Storage: Seal the container, lock it, and then store it in a well ventilated

place.

; Request a specialized waste disposer licensed by the governor Disposal

to dispose of the container and its content.

3. COMPOSITION/INFORMATION ON INGREDIENTS



Chemical name	Tin powder	Flux paste	Solid paraffin	Alicyclic amine hydrobromate	Aliphatic amine hydrobromate
Composition (%)	40-50	30-40	10-20	>10	>10
Chemical formula	Sn	C _n H _{2n+2} (n=15-20)	C _m H _{2m+2}	$C_AH_BN_C \cdot HB_r$	$C_DH_EN_F \cdot HB_r$
Official gazette reference No.	_	9-1693	8-414	Undisclosable due to confidentiality although these are existing chemical substances.	
CAS No.	7440-31-5	8009-03-8	8002-74-2		
U.N. classification	N/A	N/A	N/A	N/A	N/A
U.N. No.	_		_	_	_

4. FIRST-AID MEASURES

Eye contact: Carefully rinse the eye with water for at least 15 minutes. If the contact lens

can be removed easily, do so. Subsequently continue to rinse the eye.

Receive medical attention.

Skin contact: Immediately rinse the skin. Receive medial attention.

Remove the contaminated clothes and then machine-wash them before

reuse.

Inhalation: Move the victim to a location with fresh air and rest him in the easy-to-breath

position. Immediately receive medical attention.

Ingestion: Immediately receive medial attention.

Rinse the mouth. Do not force the victim to vomit.

Expected acute and late: Skin contact : Skin irritation, rash, rough skin, and reddening

> symptoms : Steam and mist irritate the lungs and upper

Inhalation

respiratory tract.

: The mucosa is irritated. Eye contact

Most important sign and:

symptom

5. FIRE FIGHTING MEASURES

Extinguishing media : Special powder fire-extinguisher or dry sand

Extinguishing media not : Other extinguishing media

to be used



Specific hazards : Do not use compressed water spray for fire extinction. Fire might result in

generating irritating, toxic, or corrosive gas.

The product reacts with strong oxidizer.

Special fire fighting

procedures

: If not hazardous, move the container from the fire area.

If the container cannot be moved, cool it by spraying water over the

container and the adjacent area.

Protection of fire fighters : For fire-fighting, use an appropriate air breathing apparatus and

protective wear with heat resistance.

6. ACCIDENTAL RELEASE MEASURES

Personal protection, precautions for human Immediately isolate the leakage area by defining appropriate distance in

all direction.

body, protective equipment,

and emergency measures

Prohibit access by any person other than the authorized personnel. The workers should use appropriate protective equipment (see "8.

EXPOSURE CONTROLS/PERSONAL PROTECTION") to avoid

contact with their eyes and skin and inhalation of gas.

Sweep leakage to collect it in an empty container.

Without using appropriate protective wear, do not touch any damaged

container or leakage.

Stay windward.

Keep away from any low-lying land.

Environmental Protection Take care to ensure that the product does not cause an environmental

effect by being released to any river or the like. Do not release the

product to the environment.

Method and materials for

contaminant and cleaning

up

Methods and equipment for :

containment and purification

If not hazardous, stop leakage.

Preventive measures for secondary disaster

Immediately eliminate all the ignition sources.

Clean the product remaining on the floor as frequently as possible

because the floor becomes slippery.

7. HANDLING & STORAGE

Handling

Technical measures: Take equipment measures and use protective equipment as described

in "8. EXPOSURE CONTROLS/PERSONAL PROTECTION."

Regional and general: Carry out regional and general ventilation as described in "8.

ventilation EXPOSURE CONTROLS/PERSONAL PROTECTION."



Precautions : Do not handle the product until you read and understand all the safety

precautions.

Do not inhale dust and fume.

Avoid contact with your eyes and skin.

Do not touch, inhale, or swallow the product.

When using the product, do not eat or smoke.

After handling the product, well wash your hands.

Use the product only outdoors or in a well-ventilated area.

Avoidance of contact : See "10. STABILITY AND REACTIVITY."

Storage

Technical measures: In the storage location, provide necessary equipment for natural and

electric illumination and ventilation that is required to handle the

hazardous material.

Storage conditions: Store the product while keeping away from any oxidizing agent.

Seal the container and store it in a well-ventilated location.

Dangerous material for : See "10. STABILITY AND REACTIVITY."

mixed contact

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Allowable concentration : Not specified.

Allowable concentration (exposure limit and biological exposure index)

2005 issue of journal by Japan : Not specified

Soceity for Occupational Health
Maximum allowable concentration
ACGIH 2005 issue

TLV-TWA: 2mg/m³ (as tin powder and solid paraffin)

TLV-STEL:



Measures for equipment : In the work area to store or handle the product, provide an eye shower and safety show.

> In order to maintain the concentration of production in air at a level below the exposure limit, carry out ventilation for exhaust.

If dust or fume is generated in the high-heat process, provide a ventilator to maintain an air contaminant level lower than the control concentration.

Do not handle the product without using closed equipment or a regional ventilator.

In order to maintain the aerial concentration below the recommended control concentration, make the process airtight and use regional ventilation and other equipment measures.

Protective gear

Protective gear for respiratory: Use appropriate protective gear for respiration.

Protective gloves : Use appropriate protective gloves.

Protective gear for eyes: Use appropriate protective gear for eyes.

Use safety goggles.

If contact with eyes or face can occur from splashing or spraying, use comprehensive chemical splash goggles and a

facial shield.

Protective gear for skin and body: Use appropriate protective gear for the face.

Use appropriate protective wear and boots.

Hygiene measures: Well wash your hands after handling the product.

Protective clothing:

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Appearance: Semisolid material

Color Opaque gray

Odor: None

pH: No data

Melting point/freezing point : 40°C min.

Boiling point, initial boiling point, : No data

and boiling range

Flash point : 180°C min.

Explosion range – Lower limit (%) : No data Explosion range – Upper limit (%) : No data

Vapor pressure: No data



Vapor density: No data

Specific gravity: No data

Solubility in water: No data

Octanol/water partition coefficient : No data

Spontaneous ignition temperature : No data

Decomposition temperatur : No data

Threshold for smell : No data

Evaporation rate (Butyl acetate=1) : No data

Combustibility (solid and gas) : No data

Viscosity: No data

10. STABILITY AND REACTIVITY

: The product slightly deliquesces when exposed to air. Stability / Reactivity

Potentially hazardous

reactions

: The product reacts with strong oxidizing agent, acids, strong bases,

halogen, sulfur, etc.

Conditions to be avoided : Heat source, air, and water

Incompatible materials : Strong oxidizing agent, acids, strong bases, halogen, sulfur, etc.

Hazardous decomposition

products

: The product decomposes when heated, generating hazardous fuse

(hydrogen bromide), carbon monoxide, and carbon dioxide.

11. TOXICOLOGICAL INFORMATION (Including symptom of human and epidemical information)

Acute toxicity: The product has been determined as not classified based on data showing that oral toxicity LD₅₀ in rat is larger than 5000 mg/kg (solid paraffin).

> About 80% of the components of the mixture consists of components of which toxicity is unknown.

> There are data showing that dermal toxicity LD₅₀ in rabbit is larger than 3600 mg/kg (solid paraffin). However, the product has been determined as unclassifiable. About 80% of the components of the mixture consists of components of which toxicity is unknown.

Inhalation of steam: No data is available.

Inhalation of dust: No data is available.



Skin corrosion/Skin irritation : In a rabbit test for solid paraffin, the product was evaluated as mil and not irritating. In a test applying the product to human skin, however, the product was evaluated as not irritating. Based on these data, the product has been determined as not classified.

Serious eye damage / Eye irritation : The rabbit test for solid paraffin showed that the product is slightly irritant and mild irritant. Accordingly, the product has been determined as category 2B. About 80% of the components of the mixture consists of components of which toxicity is unknown.

Eye irritation: Category 2B

Respiratory sensitization: No data

Skin sensitization: No data

Germ cell mutagenicity: No data

Carcinogenicity: No data Reproductive toxicity: No data

Specific target organ systemic toxicity - single exposure : Since the fume causes respiratory tract irritation, the product has been determined as category 3 (respiratory tract irritation).

Category 3: Potential respiratory irritation

Specific target organ systemic : toxicity - Repeated exposure

Pneumoconiosis was seen in workers handling metallic tin. Long-term exposure to this substance can cause benign pneumoconiosis (stannosis) in the lungs.

Damage to organs due to long-term or repetitive exposure (category

1): Lung

Long-term or repetitive exposure causes renal damage. Long-term or repetitive exposure causes lung damage.

Aspiration hazards : No data

12. ECOLOGICAL INFORMATION

Acute hazards to the aquatic : Unclassifiable due to data deficiency

environment

Chronic hazards to be the : Unclassifiable due to data deficiency

aquatic environment



13. DISPOSAL CONSIDERATIONS

Waste from residues:

For disposal of this product, comply with the applicable law and the local government's regulations.

When industrial waste disposers licensed by the governor or local

authorities dispose of waste, request them.

Before requesting the disposal of waste, ensure that the industrial waste disposer or local authorities are made well aware of hazards

and toxicity.

Contaminated containers and :

packages

The containers should be cleaned and then recycled or should be disposed of in accordance with the applicable law and the local government's regulations.

To dispose of empty containers, completely remove their content.

14. TRANSPORTATION INFORMATION

International regulations

Maritime transport regulations : Nonhazardous material

UN No.

Proper shipping Name

Class

Sub risk

Packing Group

Marine Pollutant : Not applicable

Information on aeronautical: Nonhazardous material

regulations

UN No.

Proper shipping Name

Class

Packing Group

Domestic regulations

Land transport regulations : Comply with the fire prevention ordinance (Solid paraffin).

Maritime transport regulations : Nonhazardous material

UN No.

Proper shipping Name

Class



Sub risk

Packing Group

Marine Pollutant

Information on aeronautical: Nonhazardous material

regulations

UN No.

Proper shipping Name

Class

Packing Group

Special safety measures : Hazardous material should be loaded so that it or its transportation

container does not drop, tumble, or get damaged.

Transport hazardous material or its container while ensuring that there

is no heavy friction or jolt.

15. REGULATORY INFORMATION

Industrial safery and health act :

Deleterioius materials whose name and other information should be notified (Article 57-2 of the law; Appendix 9 to Article 18-2 of enforcement regulations) (paraffin and tin)

Fire Defense Law:

Designated combustible material and combustible solid (Artile 9-3 of the law; Appendix 4 to Hazardous Material Regulations)

Pollutant Release and Transfer Register(PRTR)Law

Ship safety act

Civil aeronautics Act

16. OTHER INFORMATION

Reference:

Manufacturer-issued MSDS

This document has been prepared based on the information and data that are available as of this date.

Therefore, it may be revised when new information or data has been obtained.

The information and data contained herein are subject to the normal use. The evaluation of dangerousness and toxicity is, therefore, not always applicable. For this reason, the safety precautions suitable for your purpose and method must be taken prior to the use.

