

American Hakko Products, Inc.

PRODUCT BULLETIN

Bulletin No: PB413
Issue Date: 1-23-2018
Effective Date: 2-1-2018

Description/Title:

NEW HAKKO FU500 Solder feed unit

Part No:

FU500-21X, FU500-71X



Specification:

| -1, | |
|----------------------|---------------------------|
| Model | FU-500 |
| Part No. | FU500-21X (L Type) |
| (Feeder Type) | FU500-71X (Straight Type) |
| Input Voltage | 127 VAC 50/60 Hz |
| Power Consumption | 35W |
| ESD Safe | Yes |

Contents:

| FU500-21X | | FU500-71X | |
|-----------|---------------|-----------|-----------------|
| Part No. | Description | Part No. | Description |
| | FU-500 Solder | | FU-500 Solder |
| | Feed Unit | | Feed Unit |
| CX1010 | Feeder Unit | CX5006 | Feeder Unit |
| CX1010 | (L type) | CASOUG | (Straight Type) |
| BX1041 | Tube Unit | BX1041 | Tube Unit |
| | (0.3-1.0mm) | BX1041 | (0.3-1.0mm) |
| BX1042 | Tube Unit | BX1042 | Tube Unit |
| | (1.2-1.6mm) | BX1042 | (1.2-1.6mm) |
| BX1036 | Feeder Cable | BX1036 | Feeder Cable |
| B3508 | Power Cord | B3508 | Power Cord |
| BX1057 | Solder Reel | BX1057 | Solder Reel |
| | Stand | PYTO2 | Stand |
| | Instruction | | Instruction |
| | Manual | | Manual |

^{*}Solder feed pulley unit, solder feed guide set and Teflon tube sold separately based on the required solder diameter (See parts list on page 2).

Station

| Outer Dimension (W x H x D) | 145 x 100 x 230 mm | |
|-----------------------------|-----------------------|--|
| | (5.7 x 3.9 x 9.1 in.) | |
| Weight (w/o Cord) | 2.3kg (5.1 lb.) | |

Feeder unit

| For Part No. | CX1010 (L Type) | CX5006 (Straight Type) |
|----------------------------|-----------------|------------------------|
| Compatible Solder Diameter | Ø0.3 – 1.6mm | Ø0.3 – 1.6mm |
| Weight | 800g (1.8 lb.) | 800g (1.8 lb.) |



American Hakko Products, Inc.

Additional Parts List

| Part No. | Description | |
|----------|-----------------------------------|--|
| BX1000 | Solder feed pulley unit/0.3mm | |
| BX1001 | Solder feed pulley unit/0.5mm | |
| BX1002 | Solder feed pulley unit/0.6mm | |
| BX1003 | Solder feed pulley unit/0.8mm | |
| BX1004 | Solder feed pulley unit/1.0mm | |
| BX1005 | Solder feed pulley unit/1.2mm | |
| BX1006 | Solder feed pulley unit/1.6mm | |
| BX1007 | Solder feed guide set/0.3mm | |
| BX1008 | Solder feed guide set/0.5 - 1.0mm | |
| BX1009 | Solder feed guide set/1.2 – 1.6mm | |
| BX1010 | Teflon tube insert/0.3mm | |
| BX1011 | Teflon tube insert/0.5 – 0.6mm | |
| BX1012 | Teflon tube insert/0.8mm | |
| BX1013 | Teflon tube insert/1.0mm | |
| BX1014 | Teflon tube insert/1.2mm | |
| BX1015 | Teflon tube insert/1.6mm | |
| BX1016 | Tube Unit/0.3-1.0mm, 1000mm | |
| BX1017 | Tube Unit/1.2-1.6mm, 1000mm | |
| BX1018 | Guide tube | |
| BX1019 | Guide pipe/0.3mm | |
| BX1020 | Guide pipe/0.5 – 1.0mm | |
| BX1021 | Guide pipe/1.2 – 1.6mm | |
| BX1022 | Tube Unit Grommet | |
| BX1035 | Feeder Cable, 3m | |
| BX1037 | Feeder Cable, 8m | |
| BX1038 | Teflon tube insert for BX1016 | |
| BX1039 | Teflon tube insert for BX1017 | |

Comments:

HAKKO FU-500 is an intelligent solder feeding unit that, together with the HAKKO FU-601 soldering station, can be integrated with various robotic system to achieve low cost intelligent soldering automation.

The FU-500 supports solder diameter 0.3mm to 1.6mm and it allows easy adjustment of solder feed position which is critical for automatic soldering systems. System also features a compact driver unit that allows the solder feed unit to be brought closer to the iron, increase the accuracy of amount of solder feeding. Two types of feeder orientations can be chosen to adapt to different robot style.

With an optical sensor for solder movement, FU-500 can detect solder clogging, slipping and the end of the roll. The unit is also equipped with mechanism that perforates into the solder wire as countermeasure against flux and solder ball splash, and the acceptable solder wire diameter can be changed by simply replacing the pulley unit.