



PORTABLE DEPANELER **DPF-300**

Introducing the highly anticipated CHP **DPF-300** Depaneling System, a direct upgrade from the popular CHP DPF-200. The **DPF-300** adapts the quality and benefits of the DPF-200, but this new and improved dynamic system is equipped with an industrial type electric motor spindle, eliminating the need for compressed air to operate the system.

CUSTOMIZABLE GUIDES AND BITS

MILLING HEAD w/ GUIDE



- NO PROGRAMMING
- REPLACEABLE FILTER
- NO COMPRESSED AIR NEEDED
- HIGH SPEED PRECISION SPINDLE
- INTERCHANGEABLE GUIDES RANGING FROM 1.5mm - 2.5mm
- BUILT-IN VACUUM PUMP
- CUSTOMIZABLE GUIDES AVAILABLE

MACHINE ON/OFF SWITCH

ESD WORKBENCH

ADDITIONAL SUCTION HOSE



ESD CONNECTION PORT

DPF-300

Part No.	DPF-300-E
Dimensions	64 X 70 X 95 cm (25 X 28 X 37 in)
Clearance	164 X 170 cm (65 X 67 in)
Weight	73 kg (161 lbs)
Voltage	115V/60Hz
Power	1 kW
Motor spindle power	0.27 kW
Micro-spindle Speed	24,000 RPM
Noise Level	80 dB(A) ± 3 dB(A) measured at the operator position. Test FR4 thck.1.6 mm / cutter 2 mm < 2.5 m/s ²
Vibrations	Test FR4 thck.1.6 mm / cutter 2 mm
Storing temperature	-10°C to 50°C (14°F to 122°F)
Working temperature	5°C to 35°C (41°F to 95°F)
Interchangeable Guide Material	Hardened ground steel
ESD Safe	Yes
Safety Approval	

