



American Hakko Products, Inc.

P R O D U C T B U L L E T I N

Bulletin No: PB198

Issue Date: 06/25/04

Product:

FR-1418 BGA Rework System

Part No:

FR1418-01

FR1418-02

Specification:

Unless otherwise stated specifications apply to both FR1418-01 and FR1418-02

Control System/Software:

- Embedded industrial microprocessor control
- HMI operator interface with LCD read-out panel
- Real-time PID control for forced convection hot gas top heater
- Programmable, multi-step heating/cooling cycle with 100 recipe nonvolatile memory
- Password protected, operator lock-out for programmable process variables
- Teach-mode profiling



Heaters:

- Forced convection top heater
- Full area array bottom preheater—low mass infrared type. FR1418-01 one bank 12" x 10"/750W, FR1418-02 two banks 12" x 20" /1500W
- Low, medium and high gas flow settings for top heater
- True proportional control of bottom heaters (20% to 100% power)

Hardware:

- Rigid gantry structure and system base constructed of heavy-walled aluminum
- CNC machined components for stability and accurate component placement
- Factory calibrated optics
- Thermocouple input ports (2) for real-time process monitoring and development
- Precision bearings for optics, Z-Axis and X-Y gantry
- PCB holding fixture with optional adjustable bottom-side support

From...

For pricing information, please contact your local American Hakko representative or our customer service department at (661) 294-0090.

American Hakko Products, Inc.
28920 N. Avenue Williams.
Valencia, CA 91355
Tel: (661) 294-0090
Fax: (661) 294-0096
www.hakkousa.com
AHP14 Rev 2000-01

- Compliant heater head with built-in Theta adjustment
- High resolution video image vision system
- Fixed mirror

Board Handling Capacity:

- 2 inch x 2 inch minimum recommended board size
- 14 inch x 18 inch maximum recommended standard board size
- Able to repair boards with up to 2 inch tall components
- PCB thickness' up to 0.25 inch (6.4 mm)

Component Handling Capacity:

- 0.08 inch (2.0 mm) square minimum recommended component size
- 2 inch (51 mm) square maximum recommended component size
- Handles both grid array and leaded type components—BGA, CGA, QFP, LCC, TSOP, etc.
- Placement accuracy to +/-0.001 inches

Mechanical Specifications:

- Width: 28 inches
- Depth: 28 inches
- Height: 28 inches
- Weight: approximately 125 lbs
- Supply Air:
80 PSI, 5 CFM (Dry, Filtered)
1/8 inch NPT female inlet
3/8 inch (10mm) minimum supply line

Electrical Specifications:

- Volts: 120 single phase
- Amps: FR1418-01 15 amps, FR1418-02 20 amps

Comments:

Constructed of heavy-walled aluminum castings for unsurpassed precision and stability, the innovative FR-1418 BGA Rework System is a flexible system designed for the manual alignment and placement or removal of BGA, μ BGA, Flip Chip, CSP and other surface mount electronic components with precisely controlled solder reflow profiles. The system features a unique gantry style construction similar to that of a pick-and-place machine, which allows the PCB to remain stationary while the head moves to accomplish the X, Y, Z and Theta alignment. This design allows the capacity to easily rework boards up to 14 x 18 in a smaller footprint with simple board fixturing, a large preheater and powerful forced convection top heater.

The system top heater is a forced convection/hot gas type and is integrated into the automated placement head. The bottom heater is a large area, low mass infra-red heater that provides fast, efficient heating and eliminates board warping. The optical alignment system

From...

For pricing information, please contact your local American Hakko representative or our customer service department at (661) 294-0090.

American Hakko Products, Inc.
28920 N. Avenue Williams.
Valencia, CA 91355
Tel: (661) 294-0090
Fax: (661) 294-0096
www.hakkousa.com
AHP14 Rev 2000-01

uses a CCD camera with a flat mirror and beam splitting prism for easy alignment of BGA and area array devices. The camera connects to a dedicated video monitor.

The control system features a powerful microprocessor, non-volatile memory and isolated thermocouple inputs. The operator interface is an HMI with an LCD read-out panel. The system has onboard storage for 100 recipes and multi-step heating/cooling profile capabilities.

The FR-1418 is available in two standard configurations. The FR1418-01 includes one bank of low mass infrared full area array bottom preheater. The FR1418-02 includes two banks of preheaters.

Contents:

Qty	P/N	Description
2	222-510	Bottom IR Heater Lamp 500W
2	222-511	Standard Optics Lighting Bulb 75W
3	222-512	Type K 36 Ga. Thermocouple
1	222-513	Standard Vacuum Cup 0.28 Dia.
1	222-514	Optics Calibration Tip
1	222-515	Optics Calibration Plate
1	222-400	Nozzle 14 x 14 mm
1	222-401	Nozzle 18 x 18 mm
1	222-402	Nozzle 22 x 22 mm
1	222-403	Nozzle 26 x 26 mm
1	222-404	Nozzle 30 x 30 mm
1	222-405	Nozzle 34 x 34 mm

Available:

June 28,2004

For pricing information, please contact your local American Hakko representative or our customer service department at (661) 294-0090.

From...

American Hakko Products, Inc.
28920 N. Avenue Williams.
Valencia, CA 91355
Tel: (661) 294-0090
Fax: (661) 294-0096
www.hakkousa.com
AHP14 Rev 2000-01